

**PRODUCT AND COMPANY IDENTIFICATION**

Product Code PLMSD10
Product Name Plastiment SD10
Product Description Liquid concrete/mortar admixture.
Manufacturer/Supplier Sika Limited
Watchmead
Welwyn Garden City
Hertfordshire.
AL7 1BQ
tel. 01707 394444
Fax. 01707 329129

COMPOSITION/INFORMATION ON THE COMPONENTSPreparation - Hazardous ingredients (Europe)

Component	Concentration	Classification	Risk Phrases
1) Alkyl phenol ethoxylate	1.00%-2.50%	Xi	R36/38, R53
2) 2-(2 Butoxyethoxy)ethanol	1.00%-2.50%	Xi	R36

HAZARD IDENTIFICATION

Main Hazards Not classified as hazardous.

FIRST AID MEASURES

Eye Contact Immediately flood the eye with plenty of water for at least 10 minutes, holding the eye open.
Obtain medical attention if soreness or redness persists.

Skin Contact Wash skin thoroughly with soap and water.
Contaminated clothing should be washed or dry-cleaned before re-use.
Obtain medical attention if blistering occurs or redness persists.

Ingestion Wash out mouth with water. Do not induce vomiting.
Obtain medical attention.

Inhalation Unlikely to occur. However provide symptomatic medical treatment if required.

FIRE FIGHTING MEASURES

Extinguishing Media Not combustible.
Select extinguishing agent appropriate to other materials involved.

Special Hazards of Product Combustion will produce smoke, carbon dioxide and carbon monoxide.

ACCIDENTAL RELEASE MEASURES

Personal Precautions Wear appropriate protective clothing.

Environmental Precautions and Clean-up Methods Try to prevent the material from entering drains or water courses.
Advise Authorities if spillage has entered water course or sewer or has contaminated soil or vegetation.

Spillages Small spillages may be flushed with large quantities of water.
Large spillages should be collected for disposal.
Transfer into suitable containers for recovery or disposal.

**HANDLING AND STORAGE****Handling**

Avoid contact with eyes, skin and clothing.

Storage

Storage area should be: cool. out of direct sunlight.
Where outside storage of drums is unavoidable, they should be stored horizontally to avoid ingress of water.
Protect from extremes of cold.
Storage temperature should be controlled to between 5 and 25 °C.
Keep away from foodstuffs

EXPOSURE CONTROLS/PERSONAL PROTECTION**Occupational Exposure Limits - GB**

1) 2-(2-Butoxyethoxy)ethanol

None assigned.

Engineering Control Measures

Use of the basic principles of Industrial Hygiene will enable this material to be used safely.

Respiratory Protection

Respiratory protection not normally required.

Hand Protection

Wear suitable impervious gloves.

The insides of gloves must be kept scrupulously clean.

Eye Protection

Wear safety glasses if risks of accidental contamination are possible during application.

PHYSICAL AND CHEMICAL PROPERTIES**Physical State**

Liquid.

Color

Brown.

Odor

Faint. - Characteristic.

pH

9 (typical)

Boiling Point °C

>100

Flash Point °C

Not applicable.

Solubility - Water

Miscible.

Vapor Pressure (kPa)

Negligible vapour pressure at ambient conditions.

Density (kg/m³)

Approx. 1040.

Viscosity (at 20°C)

Mobile liquid at ambient temperatures.

STABILITY AND REACTIVITY**Stability**

Stable under normal conditions.

Conditions to avoid

Protect from frost

Materials to avoid

Oxidising agents. Mineral acids. Alkalis.

Hazardous Decomposition Products

Combustion will generate: oxides of carbon. oxides of sulphur.

TOXICOLOGICAL INFORMATION**Acute toxicity**

Low order of acute toxicity.

Eye irritation

May cause slight transient irritation.

Skin irritation

Frequent or prolonged skin contact may cause some local short term skin irritation.

**ECOLOGICAL INFORMATION**

<i>Mobility</i>	The product will dissolve rapidly in water.
<i>Persistence/degradability</i>	The product is expected to be readily biodegradable.
<i>Ecotoxicity</i>	The product may be harmful to aquatic organisms.

DISPOSAL

<i>Product Disposal</i>	Arrange for disposal via a licensed waste contractor.
<i>Container Disposal</i>	Dispose of containers with care. Labels should not be removed from containers until they have been cleaned. Empty packaging should be removed by a licensed waste contractor.

TRANSPORT INFORMATION

<i>ADR/RID Substance Identification Number</i>	Not Regulated under ADR/RID
<i>IMDG : Proper shipping name</i>	Not Regulated under IMDG
<i>IATA : Proper shipping name</i>	Not Regulated under ICAO

REGULATORY INFORMATION

<i>Risk Phrases</i>	None assigned.
<i>Safety Phrases</i>	The following are offered as advisory. Avoid contact with skin and eyes. In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.

OTHER INFORMATION

<i>First Issue Date</i>	31.01.2001
<i>Revisions Highlighted</i>	Future revisions will incorporate such information as is required but which is not available at this time.
<i>Uses and Restrictions</i>	Customers are urged to ensure that the product is entirely suitable for their own purpose. It is the customer's responsibility to ensure that a suitable and sufficient assessment of the risks created by the use of the product is undertaken.
<i>UK Legislation</i>	Health and Safety at Work etc Act, 1974, and relevant Statutory Provisions. SI 1999/437: The Control of Substances Hazardous to Health Regulations SI 1993/1746: Chemicals (Hazard Information and Packaging) Regulations, 1993. SI No 2839 1991 Environmental Protection (Duty of Care) Regulations.
<i>UK Guidance Publications</i>	Approved Code of Practice - Management of Health and Safety at Work, HSE. General Approved Code of Practice to COSHH Regulations, HSE. EH40, Occupational Exposure Limits, HSE. Revised Annually.



SAFETY DATA SHEET

Plastiment SD10

Date of issue - 22/03/2001.

PLMSD10

Footnote

The information contained in this SDS corresponds to our level of knowledge at the time of publication. All warranties are excluded. Our most current General Sales Conditions shall apply. Please consult the Technical Data Sheet prior to use.