

**PRODUCT AND COMPANY IDENTIFICATION**

Product Code SIKMTH30
Product Name Sikament HE 300
Product Description Chloride free accelerator for concrete.
Manufacturer/Supplier Sika Limited
Watchmead
Welwyn Garden City
Hertfordshire.
AL7 1BQ
tel. 01707 394444
Fax. 01707 329129

COMPOSITION/INFORMATION ON THE COMPONENTSPreparation - Hazardous ingredients (Europe)

Component	Concentration	Classification	Risk Phrases
1) Sodium thiocyanate	0.10%-1.00%	Xn	R20/21/22, ,, R32

HAZARD IDENTIFICATION

Main Hazards Contact with acids liberates very toxic gas.

FIRST AID MEASURES

Eye Contact Immediately flood the eye with plenty of water for at least 10 minutes, holding the eye open.
Obtain medical attention if soreness or redness persists.

Skin Contact Wash skin thoroughly with soap and water.
Contaminated clothing should be washed or dry-cleaned before re-use.
Do not use organic solvents to clean skin.

Ingestion Do not induce vomiting. Wash out mouth with water.
Obtain medical attention urgently.

Inhalation Unlikely to occur. However provide symptomatic medical treatment if required.

FIRE FIGHTING MEASURES

Extinguishing Media Not combustible.
Select extinguishing agent appropriate to other materials involved.

Special Hazards of Product Thermal decomposition or burning may release oxides of carbon, nitrogen and other toxic gases and vapours.
See also Section 10.

Protective Equipment for Fire-Fighting Wear self contained breathing apparatus.

**ACCIDENTAL RELEASE MEASURES****Personal Precautions**

Wear appropriate protective clothing.

Environmental Precautions and Clean-up Methods

Try to prevent the material from entering drains or water courses.
Advise Authorities if spillage has entered water course or sewer or has contaminated soil or vegetation.

Spillages

Small spillages may be flushed with large quantities of water.
Large spillages should be collected for disposal.
Transfer into suitable containers for recovery or disposal.

HANDLING AND STORAGE**Handling**

Avoid contact with eyes, skin and clothing.

Storage

Storage area should be: cool. out of direct sunlight.
Where outside storage of drums is unavoidable, they should be stored horizontally to avoid ingress of water.
Protect from extremes of cold.
Storage temperature should be controlled to between 5 and 25 °C.
Keep away from foodstuffs

EXPOSURE CONTROLS/PERSONAL PROTECTION**Occupational Exposure Limits - GB**

1) Sodium thiocyanate

None assigned.

Engineering Control Measures

Use of the basic principles of Industrial Hygiene will enable this material to be used safely.

Respiratory Protection

None required.

Hand Protection

Wear suitable impervious gloves.

Eye Protection

Chemical goggles if there is a risk of splashing.

PHYSICAL AND CHEMICAL PROPERTIES**Physical State**

Liquid.

Color

Brown.

Odor

Odourless.

pH

Range between 7 to 9.

Boiling Point °C

>100

Flash Point °C

Not applicable.

Solubility - Water

Miscible.

Density (kg/m³)

Approx. 1.2 at 20 °C.

Viscosity (at 20°C)

Mobile liquid at ambient temperatures.

STABILITY AND REACTIVITY**Stability**

Stable under normal conditions.

Conditions to avoid

Extremes of temperature.

Materials to avoid

Protect from frost
Strong mineral acids.
Oxidising agents.

Hazardous Decomposition Products

After evaporation of water, combustion will generate: oxides of carbon. oxides of nitrogen. oxides of sulphur. formaldehyde.

**TOXICOLOGICAL INFORMATION**

<i>Acute toxicity</i>	Low order of acute toxicity.
<i>Eye irritation</i>	May cause slight transient irritation.
<i>Skin irritation</i>	Frequent or prolonged skin contact may cause some local short term skin irritation.

ECOLOGICAL INFORMATION

<i>Mobility</i>	The product will dissolve rapidly in water.
<i>Persistence/degradability</i>	The product is expected to be not readily biodegradable.
<i>Ecotoxicity</i>	The product is expected to be slightly toxic to aquatic species.

DISPOSAL

<i>Product Disposal</i>	Arrange for disposal via a licensed waste contractor.
<i>Container Disposal</i>	Dispose of containers with care. Empty containers may contain hazardous residues. Empty packaging should be removed by a licensed waste contractor.

TRANSPORT INFORMATION

<i>UN : UN number</i>	Not classified.
<i>UN : Proper shipping name</i>	None assigned.
<i>ADR/RID Substance Identification Number</i>	Not classified.
<i>IMDG : Proper shipping name</i>	Not classified.

REGULATORY INFORMATION

<i>Risk Phrases</i>	Contact with acids liberates very toxic gas.
<i>Safety Phrases</i>	The following are offered as advisory: Avoid contact with skin and eyes. In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.

OTHER INFORMATION

<i>First Issue Date</i>	23.02.2000
<i>Revisions Highlighted</i>	Future revisions will incorporate such information as is required but which is not available at this time.
<i>Uses and Restrictions</i>	Customers are urged to ensure that the product is entirely suitable for their own purpose. It is the customer's responsibility to ensure that a suitable and sufficient assessment of the risks created by the use of the product is undertaken.



SAFETY DATA SHEET

Sikament HE 300

Date of issue - 22/03/2001.

SIKMTH30

UK Legislation

Health and Safety at Work etc Act, 1974, and relevant Statutory Provisions.
SI 1993/1746: Chemicals (Hazard Information and Packaging) Regulations, 1993.
SI 1999/437: The Control of Substances Hazardous to Health Regulations
SI No 2839 1991 Environmental Protection (Duty of Care) Regulations.

UK Guidance Publications

Approved Code of Practice - Management of Health and Safety at Work, HSE.
General Approved Code of Practice to COSHH Regulations, HSE.

Footnote

The information contained in this SDS corresponds to our level of knowledge at the time of publication. All warranties are excluded. Our most current General Sales Conditions shall apply. Please consult the Technical Data Sheet prior to use.

This page is intentionally blank



SAFETY DATA SHEET

Sikament HE 300

Date of issue - 22/03/2001.

SIKMTH30
