



Sika[®] SLC 1 Powder

Stabiliser for Concrete and Grout

Technical Data Sheet

DESCRIPTION

Sika SLC 1 is a concrete and mortar admixture used to create thixotropic self levelling concrete and mortar.

USES

- * **Sika SLC 1** can be used in the production of pre-bagged concrete and mortar products.

ADVANTAGES

- * Greatly increased cohesion
- * Single product addition
- * Extended workable life
- * Reduced bleed and segregation
- * Self levelling

Technical Data (typical)

Form:	Powder
Colour:	Buff
Specific Gravity:	0.60
Dosage % by Wt of Cement:	0.5–1.0%
Chloride Content % w/w:	Nil (less than 0.01% wt/wt)
Freezing Point °C:	-1°C

All above values are approximate.



METHOD OF USE

Trials should be carried out in combination with our Technical Department to establish optimum performance.

DISPENSING

Depending on the desired effect, type of cement and mix design, the normal dosage is between 0.5% and 1.0% by weight of cement. The powder should be distributed onto the dry aggregates or cement. Thorough mixing is essential.

COMPATIBILITY

Sika Admixtures: All
Cements: All

PACKAGING

Refer to latest price list

STORAGE AND SHELF LIFE

Sika SLC 1 should be stored in dry warehouse conditions between 5°C and 30°C. Under these conditions the product will have a minimum shelf life of 6 months. Damp or wet storage conditions will cause caking and make the product unusable.



Handling Precautions

Sika products are generally harmless provided that certain precautions normally taken when handling chemicals are observed. The materials must not, for instance, be allowed to come in contact with foodstuffs or food utensils and measures should also be taken to prevent the uncured materials from coming in contact with the skin, since people with particularly sensitive skin may be affected. The use of protective clothing, goggles, barrier creams and rubber gloves is required. The skin should be thoroughly cleaned at the end of each working period either by washing with soap and warm water or by using a resin-removing cream - the use of powerful solvents is to be avoided. Disposable paper towels - not cloth towels - should be used to dry the skin. Adequate ventilation of the working area is recommended. In case of accidental eye or mouth contact, flush with water - consult a doctor immediately. Health and Safety information on Sika Products is available and we strongly advise that this is read prior to their use. Sika products are for professional use and should be stored in sealed containers away from the reach of children.

Important Note

The information, and, in particular, the recommendations relating to the application and end-use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users should always refer to the most recent issue of the Technical Data Sheet for the product concerned, copies of which will be supplied on request.

Please consult our Technical Sales Department for further information

SIKA LIMITED

Watchmead, Welwyn Garden City, Hertfordshire, AL7 1BQ

Tel: 01707 394444 Email: sika@uk.sika.com

Fax: 01707 329129 www.sika.com

