



Sika® ViscoCrete® Stabiliser

Self Compacting Concrete Enhancing Admixture

Technical Data Sheet

DESCRIPTION

Sika ViscoCrete Stabiliser is a liquid thixotropic self compacting concrete enhancing admixture suitable for all types of **ViscoCrete** modified concrete.

USES

- * **Sika ViscoCrete Stabiliser** will help achieve self-compacting workabilities when used in conjunction with the **Sika ViscoCrete** range of superplasticisers.

ADVANTAGES

- * Assists in stabilising self-compacting concrete mixes
- * Supplied in liquid form for easy dispensing
- * Eliminates segregation and bleeding
- * Improved flow characteristics
- * Maintains workability
- * Improves surface finish

Technical Data (typical)

Form:	Liquid
Colour:	Brown
Specific Gravity:	1.21
Dosage % by Wt of Cement:	0.1–1.0% wt/wt
Chloride Content % w/w:	Nil (less than 0.1 wt/wt)
Effect on Setting:	Extends slump life
Freezing Point °C:	-5°C

All above values are approximate.



METHOD OF USE

Sika ViscoCrete Stabiliser should be used in conjunction with a Visocrete Superplasticiser.

DISPENSING

In order to obtain optimum results **Sika ViscoCrete Stabiliser** should be dispensed with the mix water.

EFFECTS OF OVERDOSING

Will retard and increase cohesion of mix.

COMPATIBILITY

Sika Admixtures: All
Cements: All

IMPORTANT NOTES


Sika ViscoCrete Stabiliser requires agitation prior to dispensing; this can be achieved by the use of an airline once per week or immediately prior to use.

PACKAGING

Refer to latest price list

STORAGE AND SHELF LIFE

Minimum 1 year in sealed containers stored in dry warehouse condition (+5°C – +25°C). Protect from frost.



Handling Precautions

Sika products are generally harmless provided that certain precautions normally taken when handling chemicals are observed. The materials must not, for instance, be allowed to come in contact with foodstuffs or food utensils and measures should also be taken to prevent the uncured materials from coming in contact with the skin, since people with particularly sensitive skin may be affected. The use of protective clothing, goggles, barrier creams and rubber gloves is required. The skin should be thoroughly cleaned at the end of each working period either by washing with soap and warm water or by using a resin-removing cream - the use of powerful solvents is to be avoided. Disposable paper towels - not cloth towels - should be used to dry the skin. Adequate ventilation of the working area is recommended. In case of accidental eye or mouth contact, flush with water - consult a doctor immediately. Health and Safety information on Sika Products is available and we strongly advise that this is read prior to their use. Sika products are for professional use and should be stored in sealed containers away from the reach of children.

Important Note

The information, and, in particular, the recommendations relating to the application and end-use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users should always refer to the most recent issue of the Technical Data Sheet for the product concerned, copies of which will be supplied on request.

Please consult our Technical Sales Department for further information

SIKA LIMITED

Watchmead, Welwyn Garden City, Hertfordshire, AL7 1BQ

Tel: 01707 394444 Email: sika@uk.sika.com

Fax: 01707 329129 www.sika.com

