



Plastiment® SD9

Admixture for Concrete Roof Tile Manufacture

Technical Data Sheet

DESCRIPTION

Sika Plastiment SD9 is a liquid admixture, especially formulated for use in extruded concrete roof tiles.

ADVANTAGES

- * Improved colour intensity - possibility to reduce pigment owing to improved dispersion in the mix
- * Greater degree of impermeability of the concrete roof tile
- * Higher strengths with existing cement contents
- * Better compaction leading to closer textured surface
- * Improved overall aesthetic appearance of tiles
- * Significant levels of cement and cost savings with no loss of concrete quality, strength or durability
- * Reduced incidence of efflorescence

BENEFITS

- * Concrete quality, colour intensity, strength and durability are all enhanced by the use of **Sika Plastiment SD9**.
- * Because it is in liquid form, **Sika Plastiment SD9**, is simple to dispense into the concrete mix.

Technical Data (typical)

Form:	Liquid
Colour:	brown
Specific Gravity:	1.174
Dosage % by Wt of cement:	0.4 - 1.0%
Chloride Content % w/w:	Nil (ie less than 0.1% w/w)
Freezing point °C:	-2°C

All above values are approximate.



METHOD OF USE

Sika Plastiment SD9 should be dispensed with the mix water into the concrete mix.

STORAGE AND SHELF LIFE

Sika Plastiment SD9 should be stored in dry conditions above 0°C in original sealed containers.

The shelf life of **Sika Plastiment SD9** under these conditions is a minimum of 12 months.



Handling Precautions

Sika products are generally harmless provided that certain precautions normally taken when handling chemicals are observed. The materials must not, for instance, be allowed to come in contact with foodstuffs or food utensils and measures should also be taken to prevent the uncured materials from coming in contact with the skin, since people with particularly sensitive skin may be affected. The use of protective clothing, goggles, barrier creams and rubber gloves is required. The skin should be thoroughly cleaned at the end of each working period either by washing with soap and warm water or by using a resin-removing cream - the use of powerful solvents is to be avoided. Disposable paper towels - not cloth towels - should be used to dry the skin. Adequate ventilation of the working area is recommended. In case of accidental eye or mouth contact, flush with water - consult a doctor immediately. Health and Safety information on Sika Products is available and we strongly advise that this is read prior to their use. Sika products are for professional use and should be stored in sealed containers away from the reach of children.

Important Note

The information, and, in particular, the recommendations relating to the application and end-use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users should always refer to the most recent issue of the Technical Data Sheet for the product concerned, copies of which will be supplied on request.

Please consult our Technical Sales Department for further information

SIKA LIMITED

Watchmead, Welwyn Garden City, Hertfordshire, AL7 1BQ

Tel: 01707 394444 Email: sika@uk.sika.com

Fax: 01707 329129 www.sika.com

