



# Sikaporo 40

## High Dosage Air Entraining and Foaming Agent

### Technical Data Sheet

#### DESCRIPTION

**Sikaporo 40** is an air-entraining agent formulated from modified naturally occurring and synthetic surfactants.

**Sikaporo 40** promotes highly air entrained concrete and via a foam generator, foam concrete.

#### USES

- \* Trench Reinstatement
- \* Voidfill
- \* Lightweight Construction

#### ADVANTAGES

- \* **Sikaporo 40** is manufactured by Sika Limited under strict control from carefully selected raw materials of consistent quality
- \* **Sikaporo 40** can produce highly air entrained mortars or concrete
- \* **Sikaporo 40** via a foam gun ca produce foamed concrete and mortar as low as 500 Kg/metre

#### Technical Data (typical)

<b>Form:</b>	Liquid
<b>Colour:</b>	Clear
<b>Specific Gravity:</b>	1.05
<b>Chloride Content % w/w:</b>	Nil
<b>Freezing Point °C:</b>	-1°C

All above values are approximate.



## METHOD OF USE

Both mixes will be high flow and easily placed.

## DISPENSING

Standard dispenser for High AE concrete.  
Foam Gun for Foamed mortar/concrete.

## COMPATIBILITY

**Sika Admixtures:** All  
**Cements:** All

## IMPORTANT NOTES

A foam gun will produce a greatly enhanced performance.

## PACKAGING

Refer to latest price list

## STORAGE AND SHELF LIFE

Minimum 1 year in sealed containers stored in dry warehouse condition (+5°C – +25°C). Protect from frost.



### Handling Precautions

Sika products are generally harmless provided that certain precautions normally taken when handling chemicals are observed. The materials must not, for instance, be allowed to come in contact with foodstuffs or food utensils and measures should also be taken to prevent the uncured materials from coming in contact with the skin, since people with particularly sensitive skin may be affected. The use of protective clothing, goggles, barrier creams and rubber gloves is required. The skin should be thoroughly cleaned at the end of each working period either by washing with soap and warm water or by using a resin-removing cream - the use of powerful solvents is to be avoided. Disposable paper towels - not cloth towels - should be used to dry the skin. Adequate ventilation of the working area is recommended. In case of accidental eye or mouth contact, flush with water - consult a doctor immediately. Health and Safety information on Sika Products is available and we strongly advise that this is read prior to their use. Sika products are for professional use and should be stored in sealed containers away from the reach of children.

### Important Note

The information, and, in particular, the recommendations relating to the application and end-use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users should always refer to the most recent issue of the Technical Data Sheet for the product concerned, copies of which will be supplied on request.

**Please consult our Technical Sales Department for further information**

SIKA LIMITED

Watchmead, Welwyn Garden City, Hertfordshire, AL7 1BQ

Tel: 01707 394444 Email: [sika@uk.sika.com](mailto:sika@uk.sika.com)

Fax: 01707 329129 [www.sika.com](http://www.sika.com)

