



# Sikafloor<sup>®</sup> EpoCem<sup>®</sup> Module

## Water Based Primer

### Technical Data Sheet

#### DESCRIPTION

Sikafloor **EpoCem Module** is a clear two component, solvent free waterbased epoxy resin dispersion.

#### USES

- \* As a primer for **Sikafloor 81/82 EpoCem**.
- \* A resin binder for all **EpoCem** products
- \* Seals concrete and screeds.

#### ADVANTAGES

- \* Excellent primer coat.
- \* Easy to use.
- \* Low viscosity.
- \* Waterbased.
- \* Reduces permeability.
- \* Reduces dusting.
- \* Economical.
- \* Pre-dosed units.

#### FLOOR COATING SYSTEM:

**Primer coat:** 1 - 2 x **Sikafloor EpoCem Module**.

**Seal coat:** 1 - 3 x **Sikafloor EpoCem Module**.

**Material consumption:** Approx 0.2 - 0.3 kg/m<sup>2</sup> per coat.

#### Technical Data (typical)

<b>Colour:</b>	Transparent.
<b>Density (SG):</b>	Approx 1.0 kg/litre
<b>Application temperatures &amp; humidity conditions:</b>	+8°C min, +30°C max (Substrate and ambient) RH 80% max
<b>Substrate M.C. &amp; RH:</b>	≤12% by Wt or ≤95% RH
<b>Additional application information:</b>	+20°C
<b>Pot life:</b>	45 mins End of pot life not noticeable
<b>Waiting time between coats:</b>	
min	12 hrs
max	36 hrs

All above values are approximate.



