

**PRODUCT AND COMPANY IDENTIFICATION**

<b>Product Code</b>	SKFL253A
<b>Product Name</b>	Sikafloor 2530W Part A
<b>Product Description</b>	2-component water dispersed epoxy resin based coating for walls and floors.
<b>Manufacturer/Supplier</b>	Sika Limited Watchmead Welwyn Garden City Hertfordshire. AL7 1BQ tel. 01707 394444 Fax. 01707 329129

**COMPOSITION/INFORMATION ON THE COMPONENTS****Preparation - Hazardous ingredients ( Europe )**

<b>Component</b>		<b>Concentration</b>	<b>Classification</b>	<b>Risk Phrases</b>
1) Polyamine-adduct		10.00%-25.00%	Xi	R41
2) Benzyl Alcohol	100-51-6	2.50% -10.00%	Xn	R20/22
3) Isophoronediamine	2855-13-2	1.00% 2.50%	C	R21/22, R34, R43, R52/53

**HAZARD IDENTIFICATION**

<b>Main Hazards</b>	Risk of serious damage to eyes. May cause sensitisation by skin contact.  Misuse of this product due to lack of personal protection or care may result in dermatitis
---------------------	---

**FIRST AID MEASURES**

<b>Eye Contact</b>	Immediately flood the eye with plenty of water for at least 15 minutes, holding the eye open. Obtain medical attention urgently.
<b>Skin Contact</b>	Wipe off as much as possible with a clean dry cloth. Wash skin thoroughly with soap and water. If material proves difficult to remove, use suitable skin cleanser (not solvent). Solvents should not be used to clean skin because they may increase the penetration of the material. Obtain medical attention if blistering occurs or redness persists. Contaminated clothing should be washed or dry-cleaned before re-use.
<b>Ingestion</b>	Do not induce vomiting. Wash out mouth with water. Obtain medical attention urgently.
<b>Inhalation</b>	Remove from exposure. Seek medical attention if you feel unwell.



**SAFETY DATA SHEET**  
**Sikafloor 2530W Part A**

Date of issue - 31/01/2002.

SKFL253A

**FIRE FIGHTING MEASURES**

<i>Extinguishing Media</i>	Not readily combustible. Use foam, dry chemical or carbon dioxide.
<i>Extinguishing Media - Not suitable</i>	Do not use water jet.
<i>Special Hazards of Product</i>	This product may give rise to hazardous fumes in a fire.
<i>Protective Equipment for Fire-Fighting</i>	Wear full protective clothing and self-contained breathing apparatus.

**ACCIDENTAL RELEASE MEASURES**

<i>Personal Precautions</i>	Wear appropriate protective clothing.
<i>Environmental Precautions and Clean-up Methods</i>	Try to prevent the material from entering drains or water courses.
<i>Spillages</i>	Contain and absorb using earth, sand or other inert material. Transfer into suitable containers for recovery or disposal.

**HANDLING AND STORAGE**

<i>Handling</i>	Use in well ventilated area. Avoid contact with eyes, skin and clothing.
<i>Storage</i>	Storage area should be: cool. dry. Protect from extremes of cold. Storage temperature should be controlled to between 5 and 25 °C. Store in the original container securely closed . Keep away from foodstuffs

**EXPOSURE CONTROLS/PERSONAL PROTECTION**

<i>Engineering Control Measures</i>	Use of the basic principles of Industrial Hygiene will enable this material to be used safely.
<i>Respiratory Protection</i>	Respiratory protection not normally required.
<i>Hand Protection</i>	Wear suitable impervious gloves. (butyl / nitrile) The insides of gloves must be kept scrupulously clean.
<i>Eye Protection</i>	Chemical goggles.

**PHYSICAL AND CHEMICAL PROPERTIES**

<i>Physical State</i>	Liquid.
<i>Color</i>	Various
<i>Odor</i>	Ammoniacal.
<i>pH</i>	Approx. 9
<i>Boiling Point °C</i>	>100
<i>Flash Point °C</i>	Not applicable.
<i>Solubility - Water</i>	Miscible.
<i>Density (kg/m<sup>3</sup>)</i>	Approx. 1300 at 20 °C.
<i>Viscosity ( at 20°C )</i>	Mobile liquid at ambient temperatures.



**SAFETY DATA SHEET**  
**Sikafloor 2530W Part A**

Date of issue - 31/01/2002.

SKFL253A

**STABILITY AND REACTIVITY**

<i>Stability</i>	Stable under normal conditions.
<i>Conditions to avoid</i>	Extremes of temperature.
<i>Hazardous Decomposition Products</i>	Combustion will generate: oxides of carbon. oxides of nitrogen. acrid smoke and irritating fumes.

**TOXICOLOGICAL INFORMATION**

<i>Eye irritation</i>	The product should be considered as a severe eye irritant.
<i>Skin irritation</i>	The product should be considered as a moderate skin irritant.
<i>Sensitization - Skin</i>	The possibility of allergic sensitisation should be considered.

**ECOLOGICAL INFORMATION**

<i>Mobility</i>	The product will dissolve rapidly in water.
<i>Persistence/degradability</i>	The product is expected to be not readily biodegradable.
<i>Ecotoxicity</i>	The product may be harmful to aquatic organisms.


**DISPOSAL**

<i>Product Disposal</i>	Dispose of as Special Waste. Arrange for disposal via a licensed waste contractor.
<i>Container Disposal</i>	Dispose of containers with care. Empty containers may contain hazardous residues. Empty packaging should be removed by a licensed waste contractor.

**TRANSPORT INFORMATION**

<i>ADR/RID Substance Identification Number</i>	Not Regulated under ADR/RID
<i>IMDG : Proper shipping name</i>	Not Regulated under IMDG
<i>IATA : Proper shipping name</i>	Not Regulated under ICAO

**REGULATORY INFORMATION**

<i>Label Requirements</i>	Irritant 
<i>Risk Phrases</i>	Risk of serious damage to eyes. May cause sensitisation by skin contact.
<i>Safety Phrases</i>	Avoid contact with skin. In case of contact with eyes, rinse immediately with plenty of water and seek medical advice. Wear suitable gloves and eye/face protection.



**SAFETY DATA SHEET**  
**Sikafloor 2530W Part A**

Date of issue - 31/01/2002.

SKFL253A

**OTHER INFORMATION**

***First Issue Date***

10.11.1997

***Revisions Highlighted***

S phrases

***Uses and Restrictions***

Customers are urged to ensure that the product is entirely suitable for their own purpose. It is the customer's responsibility to ensure that a suitable and sufficient assessment of the risks created by the use of the product is undertaken.

***UK Legislation***

Health and Safety at Work etc Act, 1974, and relevant Statutory Provisions.

SI 1993/1746: Chemicals (Hazard Information and Packaging) Regulations, 1993.

SI 1999/437: The Control of Substances Hazardous to Health Regulations

SI No. 972/1996: The Special Waste Regulations 1996

SI No 2839 1991 Environmental Protection (Duty of Care) Regulations.

***UK Guidance Publications***

General Approved Code of Practice to COSHH Regulations, HSE.

***Footnote***

The information contained in this SDS corresponds to our level of knowledge at the time of publication. All warranties are excluded. Our most current General Sales Conditions shall apply. Please consult the Technical Data Sheet prior to use.

**PRODUCT AND COMPANY IDENTIFICATION**

<b>Product Code</b>	SKFL253B
<b>Product Name</b>	Sikafloor 2530W Part B
<b>Product Description</b>	2-component water dispersed epoxy resin based coating for walls and floors.
<b>Manufacturer/Supplier</b>	Sika Limited Watchmead Welwyn Garden City Hertfordshire. AL7 1BQ tel. 01707 394444 Fax. 01707 329129

**COMPOSITION/INFORMATION ON THE COMPONENTS****Preparation - Hazardous ingredients ( Europe )**

<b>Component</b>		<b>Concentration</b>	<b>Classification</b>	<b>Risk Phrases</b>
1) Epoxy resin ( No.Av. mol.wt. < 700)	25068-38-6	25.00% -50.00%	Xi, N	R36/38, R43, R51/53
2) Aliphatic glycidyl ether	68609-97-2	2.50% - 10.00%	Xi, N	R38, R43, R51/53

**HAZARD IDENTIFICATION**

<b>Main Hazards</b>	Irritating to eyes and skin. May cause sensitisation by skin contact. Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
---------------------	---

**FIRST AID MEASURES**

<b>Eye Contact</b>	Immediately flood the eye with plenty of water for at least 15 minutes, holding the eye open. Obtain medical attention urgently.
<b>Skin Contact</b>	Wipe off as much as possible with a clean dry cloth. Wash skin thoroughly with soap and water. If material proves difficult to remove, use suitable skin cleanser (not solvent). Solvents should not be used to clean skin because they may increase the penetration of the material. Obtain medical attention if blistering occurs or redness persists. Contaminated clothing should be washed or dry-cleaned before re-use.
<b>Ingestion</b>	Do not induce vomiting. Wash out mouth with water. Obtain medical attention.
<b>Inhalation</b>	Remove from exposure. Seek medical attention if you feel unwell.

**FIRE FIGHTING MEASURES**

<b>Extinguishing Media</b>	Not readily combustible. Use foam, dry chemical or carbon dioxide.
<b>Extinguishing Media - Not suitable</b>	Do not use water jet.
<b>Special Hazards of Product</b>	Combustion will produce smoke, carbon dioxide and carbon monoxide.
<b>Protective Equipment for Fire-Fighting</b>	Wear full protective clothing and self-contained breathing apparatus.



**SAFETY DATA SHEET**  
**Sikafloor 2530W Part B**

Date of issue - 31/01/2002.

SKFL253B

**ACCIDENTAL RELEASE MEASURES**

<i>Personal Precautions</i>	Wear appropriate protective clothing.
<i>Environmental Precautions and Clean-up Methods</i>	Try to prevent the material from entering drains or water courses.
<i>Spillages</i>	Contain and absorb using earth, sand or other inert material. Transfer into suitable containers for recovery or disposal.

**HANDLING AND STORAGE**

<i>Handling</i>	Use in well ventilated area. Avoid contact with eyes, skin and clothing.
<i>Storage</i>	Protect from frost Storage area should be: cool. dry. Storage temperature should be controlled to between 5 and 25 °C. Store in the original container securely closed . Keep away from foodstuffs

**EXPOSURE CONTROLS/PERSONAL PROTECTION**

<i>Engineering Control Measures</i>	Use of the basic principles of Industrial Hygiene will enable this material to be used safely.
<i>Respiratory Protection</i>	Respiratory protection not normally required.
<i>Hand Protection</i>	Wear suitable impervious gloves. (butyl / nitrile) The insides of gloves must be kept scrupulously clean.
<i>Eye Protection</i>	Chemical goggles.

**PHYSICAL AND CHEMICAL PROPERTIES**

<i>Physical State</i>	Liquid.
<i>Color</i>	White.
<i>Odor</i>	Odourless.
<i>pH</i>	Range between 7 to 8.
<i>Flash Point °C</i>	Not applicable.
<i>Solubility - Water</i>	Miscible.
<i>Density (kg/m3)</i>	Approx. 1100 at 20 °C.
<i>Viscosity ( at 20°C )</i>	Mobile liquid at ambient temperatures.

**STABILITY AND REACTIVITY**

<i>Stability</i>	Stable under normal conditions.
<i>Conditions to avoid</i>	Extremes of temperature.
<i>Hazardous Decomposition Products</i>	Heating may produce: oxides of carbon. acrid smoke and irritating fumes.

**TOXICOLOGICAL INFORMATION**

<i>Acute toxicity</i>	Low order of acute toxicity.
<i>Eye irritation</i>	The product will be a moderate eye irritant.
<i>Skin irritation</i>	The product should be considered as a moderate skin irritant.
<i>Sensitization - Skin</i>	The low molecular weight epoxy resin is a potential skin sensitiser.



**SAFETY DATA SHEET**  
**Sikafloor 2530W Part B**

Date of issue - 31/01/2002.

SKFL253B

**ECOLOGICAL INFORMATION**

<i>Mobility</i>	Emulsifiable in water.
<i>Persistence/degradability</i>	The product is expected to be not readily biodegradable.
<i>Ecotoxicity</i>	The product may be harmful to aquatic organisms.


**DISPOSAL**

<i>Product Disposal</i>	Dispose of as Special Waste. Arrange for disposal via a licensed waste contractor.
<i>Container Disposal</i>	Dispose of containers with care. Empty containers may contain hazardous residues. Empty packaging should be removed by a licensed waste contractor.

**TRANSPORT INFORMATION**

<i>ADR/RID Substance Identification Number</i>	3082
<i>ADR/RID Proper shipping name</i>	Environmentally hazardous substance, liquid, n.o.s. Contains Epoxy Resin
<i>ADR/RID Class</i>	9
<i>ADR/RID Item Number</i>	11(c)
<i>ADR/RID Hazard Identification Number</i>	90
<i>IMDG : Proper shipping name</i>	Environmentally hazardous substance, liquid, n.o.s. contains Epoxy Resin
<i>IMDG : Packing Group</i>	3
<i>IMDG : Class</i>	9
<i>IATA : Proper shipping name</i>	Not Hazardous under IATA

**REGULATORY INFORMATION**

<i>Label Requirements</i>	Irritant, Dangerous for the environment 
<i>Risk Phrases</i>	Irritating to eyes and skin. May cause sensitisation by skin contact. Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
<i>Safety Phrases</i>	Avoid contact with skin. Wear suitable gloves. Do not empty into drains. If swallowed, seek medical advice immediately and show this container or label.  Contains epoxy constituents. See information supplied by the manufacturer.



**SAFETY DATA SHEET**  
**Sikafloor 2530W Part B**

Date of issue - 31/01/2002.

SKFL253B

**OTHER INFORMATION**

***First Issue Date***

10.11.1997

***Revisions Highlighted***

Main Hazards  
Regulatory Information

***Uses and Restrictions***

Customers are urged to ensure that the product is entirely suitable for their own purpose. It is the customer's responsibility to ensure that a suitable and sufficient assessment of the risks created by the use of the product is undertaken.

***UK Legislation***

Health and Safety at Work etc Act, 1974, and relevant Statutory Provisions.  
SI 1993/1746: Chemicals (Hazard Information and Packaging) Regulations, 1993.  
SI 1999/437: The Control of Substances Hazardous to Health Regulations  
SI No. 972/1996: The Special Waste Regulations 1996  
SI No 2839 1991 Environmental Protection (Duty of Care) Regulations.

***UK Guidance Publications***

General Approved Code of Practice to COSHH Regulations, HSE.

***Footnote***

The information contained in this SDS corresponds to our level of knowledge at the time of publication. All warranties are excluded. Our most current General Sales Conditions shall apply. Please consult the Technical Data Sheet prior to use.