

**PRODUCT AND COMPANY IDENTIFICATION**

Product Code SGD62A
Product Name Sikagard 62 Part A
Product Description Two component high build,solvent-free,protective coating based on epoxy resin.
Manufacturer/Supplier Sika Limited
Watchmead
Welwyn Garden City
Hertfordshire.
AL7 1BQ
tel. 01707 394444
Fax. 01707 329129

COMPOSITION/INFORMATION ON THE COMPONENTS**Preparation - Hazardous ingredients (Europe)**

Component		Concentration	Classification	Risk Phrases
1) Epoxy resin (No.Av. mol.wt. < 700)	25068-38-6	50.00% - 100.00%	Xi, N	R36/38, R43, R51/53
2) Aliphatic glycidyl ether	68609-97-2	2.50% - 10.00%	Xi, N	R38, R43, R51/53

HAZARD IDENTIFICATION

Main Hazards Irritating to eyes and skin.
May cause sensitization by skin contact.
Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

FIRST AID MEASURES

Eye Contact Immediately flood the eye with plenty of water for at least 15 minutes, holding the eye open.
Obtain medical attention urgently.

Skin Contact Wipe off as much as possible with a clean dry cloth. Wash skin thoroughly with soap and water.
Solvents should not be used to clean skin because they may increase the penetration of the material.

Ingestion Wash out mouth with water. Obtain medical attention.

Inhalation Remove from exposure. In cases of possible respiratory irritation or if feeling unwell in cases of prolonged exposure,obtain medical attention.

FIRE FIGHTING MEASURES

Extinguishing Media Not readily combustible.
Use foam, dry chemical or carbon dioxide.

Extinguishing Media - Not suitable Do not use water jet.

Special Hazards of Product Combustion will produce smoke,carbon dioxide and carbon monoxide.

Protective Equipment for Fire-Fighting Wear full protective clothing and self-contained breathing apparatus.

**ACCIDENTAL RELEASE MEASURES**

<i>Personal Precautions</i>	Wear appropriate protective clothing.
<i>Environmental Precautions and Clean-up Methods</i>	Try to prevent the material from entering drains or water courses.
<i>Spillages</i>	Contain and absorb using earth, sand or other inert material. Transfer into suitable containers for recovery or disposal.

HANDLING AND STORAGE

<i>Handling</i>	Use in well ventilated area. Avoid contact with eyes, skin and clothing.
<i>Storage</i>	Storage area should be: cool. dry. Storage temperature should be controlled to between 5 and 25 °C. Store in the original container securely closed . Keep away from foodstuffs

EXPOSURE CONTROLS/PERSONAL PROTECTION

<i>Engineering Control Measures</i>	Use of the basic principles of Industrial Hygiene will enable this material to be used safely.
<i>Respiratory Protection</i>	Respiratory protection not normally required.
<i>Hand Protection</i>	Wear suitable impervious gloves. (butyl / nitrile type) The insides of gloves must be kept scrupulously clean.
<i>Eye Protection</i>	Chemical goggles.

PHYSICAL AND CHEMICAL PROPERTIES

<i>Physical State</i>	Liquid.
<i>Color</i>	Various
<i>Odor</i>	Faint. Characteristic.
<i>pH</i>	Not applicable.
<i>Flash Point °C</i>	Exceeds 100.
<i>Solubility - Water</i>	Immiscible.
<i>Density (kg/m³)</i>	Approx. 1400 at 20 °C.
<i>Viscosity (at 20°C)</i>	8000-10000 (measured as mPa.s)

STABILITY AND REACTIVITY

<i>Stability</i>	Stable under normal conditions.
<i>Hazardous Decomposition Products</i>	Heating may produce: oxides of carbon. acrid smoke and irritating fumes.

TOXICOLOGICAL INFORMATION

<i>Acute toxicity</i>	Low order of acute toxicity.
<i>Eye irritation</i>	Irritating to the eyes.
<i>Skin irritation</i>	Frequent or prolonged skin contact may cause some local short term skin irritation.
<i>Sensitization - Skin</i>	The low molecular weight epoxy resin is a potential skin sensitizer. The possibility of allergic sensitisation should be considered



SAFETY DATA SHEET
Sikagard 62 Part A

Date of issue - 11/06/2002.

SGD62A

ECOLOGICAL INFORMATION

<i>Mobility</i>	The product is insoluble in water.
<i>Persistence/degradability</i>	The product is expected to be not readily biodegradable.
<i>Ecotoxicity</i>	This material is harmful to aquatic organisms.


DISPOSAL

<i>Product Disposal</i>	Dispose of as Special Waste. Arrange for disposal via a licensed waste contractor.
<i>Container Disposal</i>	Dispose of containers with care. Empty containers may contain hazardous residues. Empty packaging should be removed by a licensed waste contractor.

TRANSPORT INFORMATION

<i>ADR/RID Substance Identification Number</i>	3082
<i>ADR/RID Proper shipping name</i>	Environmentally hazardous substance, liquid, n.o.s. contains Epoxy Resin
<i>ADR/RID Class</i>	9
<i>ADR/RID Item Number</i>	11 (c)
<i>ADR/RID Hazard Identification Number</i>	90
<i>IMDG : Proper shipping name</i>	Environmentally hazardous substance, liquid, n.o.s. contains Epoxy Resin
<i>IMDG : Packing Group</i>	3
<i>IMDG : Class</i>	9
<i>IATA : Proper shipping name</i>	Not Regulated under ICAO

REGULATORY INFORMATION

<i>Label Requirements</i>	Irritant, Dangerous for the environment 
<i>Risk Phrases</i>	Irritating to eyes and skin. May cause sensitisation by skin contact. Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
<i>Safety Phrases</i>	Avoid contact with skin. Wear suitable gloves. Contains epoxy constituents. See information supplied by the manufacturer.

OTHER INFORMATION

<i>First Issue Date</i>	24.04.1995
<i>Revisions Highlighted</i>	Hazards Identification Regulatory Information
<i>Uses and Restrictions</i>	Customers are urged to ensure that the product is entirely suitable for their own purpose. It is the customer's responsibility to ensure that a suitable and sufficient assessment of the risks created by the use of the product is undertaken.



SAFETY DATA SHEET

Sikagard 62 Part A

Date of issue - 11/06/2002.

SGD62A

UK Legislation

Health and Safety at Work etc Act, 1974, and relevant Statutory Provisions.
Chemicals (Hazard Information and Packaging) Regulations, 2002.
SI 1999/437: The Control of Substances Hazardous to Health Regulations
SI No. 972/1996: The Special Waste Regulations 1996
SI No 2839 1991 Environmental Protection (Duty of Care) Regulations.

UK Guidance Publications

General Approved Code of Practice to COSHH Regulations, HSE.
Approved Code of Practice - Management of Health and Safety at Work, HSE.
EH26, Occupational Skin Diseases: Health and Safety Precautions, HSE.

Footnote

The information contained in this SDS corresponds to our level of knowledge at the time of publication. All warranties are excluded. Our most current General Sales Conditions shall apply. Please consult the Technical Data Sheet prior to use.

**PRODUCT AND COMPANY IDENTIFICATION**

Product Code SGD62B
Product Name Sikagard 62 Part B
Product Description Two component high build, solvent-free, protective coating based on epoxy resin.
Manufacturer/Supplier Sika Limited
Watchmead
Welwyn Garden City
Hertfordshire.
AL7 1BQ
tel. 01707 394444
Fax. 01707 329129

COMPOSITION/INFORMATION ON THE COMPONENTSPreparation - Hazardous ingredients (Europe)

Component		Concentration	Classification	Risk Phrases
1) Benzyl Alcohol	100-51-6	25.00% - 50.00%	Xn	R20/22
2) Trimethylhexamethylene diamine	25620-58-0	25.00% - 50.00%	C	R22, R34, R43, R52/53
3) Isophoronediamine	2855-13-2	10.00% - 25.00%	C	R21/22, R34, R43, R52/53

HAZARD IDENTIFICATION

Main Hazards Causes burns.
May cause sensitisation by skin contact.
Harmful by inhalation and if swallowed.
Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

FIRST AID MEASURES

Eye Contact Immediately flood the eye with plenty of water for at least 15 minutes, holding the eye open.
Eyelids should be held away from the eyeball to ensure thorough rinsing.
Obtain medical attention urgently.

Skin Contact Wipe off as much as possible with a clean dry cloth.
If material proves difficult to remove, use suitable skin cleanser (not solvent).
Solvents should not be used to clean skin because they may increase the penetration of the material.
Contaminated clothing should be washed or dry-cleaned before re-use.

Ingestion Do not induce vomiting.
Obtain medical attention.

Inhalation Remove from exposure.
In cases of possible respiratory irritation or if feeling unwell in cases of prolonged exposure, obtain medical attention.



SAFETY DATA SHEET

Sikagard 62 Part B

Date of issue - 11/06/2002.

SGD62B

FIRE FIGHTING MEASURES

<i>Extinguishing Media</i>	Not readily combustible. Use foam, dry chemical or carbon dioxide.
<i>Extinguishing Media - Not suitable</i>	Do not use water jet.
<i>Special Hazards of Product</i>	Thermal decomposition or burning may release oxides of carbon, nitrogen and other toxic gases and vapours.
<i>Protective Equipment for Fire-Fighting</i>	Wear full protective clothing and self-contained breathing apparatus.

ACCIDENTAL RELEASE MEASURES

<i>Personal Precautions</i>	Wear appropriate protective clothing.
<i>Environmental Precautions and Clean-up Methods</i>	Try to prevent the material from entering drains or water courses.
<i>Spillages</i>	Contain and absorb using earth, sand or other inert material. Transfer into suitable containers for recovery or disposal.

HANDLING AND STORAGE

<i>Handling</i>	Mix in a well ventilated area. Avoid contact with eyes, skin and clothing.
<i>Storage</i>	Storage area should be: cool. dry. Storage temperature should be controlled to between 5 and 25 °C. Store in the original container securely closed . Keep away from foodstuffs

EXPOSURE CONTROLS/PERSONAL PROTECTION

<i>Engineering Control Measures</i>	Use of the basic principles of Industrial Hygiene will enable this material to be used safely.
<i>Respiratory Protection</i>	Respiratory protection not normally required.
<i>Hand Protection</i>	Wear suitable impervious gloves. (butyl / nitrile type) The insides of gloves must be kept scrupulously clean.
<i>Eye Protection</i>	Chemical goggles.

PHYSICAL AND CHEMICAL PROPERTIES

<i>Physical State</i>	Liquid.
<i>Color</i>	Straw - Clear.
<i>Odor</i>	Amine like.
<i>Flash Point °C</i>	Exceeds 100.
<i>Solubility - Water</i>	Partially soluble.
<i>Density (kg/m3)</i>	Approx. 1020 at 20 °C.
<i>Viscosity (at 20°C)</i>	1000-1300 (measured as mPa.s)

STABILITY AND REACTIVITY

<i>Stability</i>	Stable under normal conditions.
<i>Hazardous Decomposition Products</i>	Heating may produce: ammonia. oxides of carbon. oxides of nitrogen. acrid smoke and irritating fumes.



TOXICOLOGICAL INFORMATION

<i>Acute toxicity</i>	Low order of acute toxicity.
<i>Eye irritation</i>	Liquid and vapour can cause irritation on contact and at high concentrations.
<i>Skin irritation</i>	This material is corrosive to the skin.
<i>Sensitization - Skin</i>	The possibility of allergic sensitisation should be considered.

ECOLOGICAL INFORMATION

<i>Mobility</i>	The product is sparingly soluble in water.
<i>Persistence/degradability</i>	The product is expected to be not readily biodegradable.
<i>Ecotoxicity</i>	This material is harmful to aquatic organisms.

DISPOSAL

<i>Product Disposal</i>	Dispose of as Special Waste. Arrange for disposal via a licensed waste contractor.
<i>Container Disposal</i>	Empty containers may contain hazardous residues. Dispose of containers with care. Empty packaging should be removed by a licensed waste contractor.

TRANSPORT INFORMATION

<i>UN : UN number</i>	1760
<i>UN : Proper shipping name</i>	Corrosive liquid, n.o.s.
<i>UN : Class</i>	8
<i>UN : Packing Group</i>	3
<i>ADR/RID Substance Identification Number</i>	1760
<i>ADR/RID Proper shipping name</i>	Corrosive liquid, n.o.s. contains Trimethylhexamethylenediamines
<i>ADR/RID Class</i>	8
<i>ADR/RID Item Number</i>	66 (c)
<i>ADR/RID Hazard Identification Number</i>	80
<i>IMDG : Proper shipping name</i>	Corrosive liquid, N.O.S. contains Trimethylhexamethylenediamines
<i>IMDG : Packing Group</i>	3
<i>IMDG : Class</i>	8
<i>IMDG : Ems Number</i>	8-15
<i>IATA : Proper shipping name</i>	Corrosive liquid, N.O.S. contains Trimethylhexmethylenediamines
<i>IATA : Packing Group</i>	3
<i>IATA : Class</i>	8



SAFETY DATA SHEET
Sikagard 62 Part B

Date of issue - 11/06/2002.

SGD62B

REGULATORY INFORMATION

Label Requirements

Corrosive



Risk Phrases

Causes burns.
May cause sensitisation by skin contact.
Harmful by inhalation and if swallowed.
Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

Safety Phrases

Avoid contact with skin.
In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible).
Wear suitable protective clothing, gloves and eye/face protection.

OTHER INFORMATION

First Issue Date

24.04.1995

Revisions Highlighted

Hazards Identification
Regulatory Information

Uses and Restrictions

Customers are urged to ensure that the product is entirely suitable for their own purpose. It is the customer's responsibility to ensure that a suitable and sufficient assessment of the risks created by the use of the product is undertaken.

UK Legislation

Health and Safety at Work etc Act, 1974, and relevant Statutory Provisions.
Chemicals (Hazard Information and Packaging) Regulations, 2002.
SI 1999/437: The Control of Substances Hazardous to Health Regulations
SI No 2839 1991 Environmental Protection (Duty of Care) Regulations.
SI No. 972/1996: The Special Waste Regulations 1996

UK Guidance Publications

Approved Code of Practice - Management of Health and Safety at Work, HSE.
EH26, Occupational Skin Diseases: Health and Safety Precautions, HSE.
General Approved Code of Practice to COSHH Regulations, HSE.

Footnote

The information contained in this SDS corresponds to our level of knowledge at the time of publication. All warranties are excluded. Our most current General Sales Conditions shall apply. Please consult the Technical Data Sheet prior to use.