

**1. PRODUCT AND COMPANY IDENTIFICATION**

<i>Product Code</i>	SGDELS675
<i>Product Name</i>	SikaGard Elastocolor 675W
<i>Product Description</i>	Water based pigmented elastomeric protective coating for concrete.
<i>Manufacturer/Supplier</i>	Sika Limited Watchmead Welwyn Garden City Hertfordshire. AL7 1BQ tel. 01707 394444 Fax. 01707 329129

2. COMPOSITION/INFORMATION ON THE COMPONENTS

<i>Hazardous ingredients</i>	The product does not contain any substances classified as hazardous under current regulations.
<i>Chemical Characteristic</i>	Pigmented paint based on aqueous copolymer dispersion.

3. HAZARD IDENTIFICATION

<i>Main Hazards</i>	Not classified as hazardous.
---------------------	------------------------------

4. FIRST AID MEASURES

<i>Eye Contact</i>	Immediately flood the eye with plenty of water for at least 15 minutes, holding the eye open. Obtain medical attention if soreness or redness persists.
<i>Skin Contact</i>	Wash skin thoroughly with soap and water. If material proves difficult to remove, use suitable skin cleanser (not solvent). Contaminated clothing should be washed or dry-cleaned before re-use.
<i>Ingestion</i>	Do not induce vomiting. Obtain medical attention.
<i>Inhalation</i>	Remove from exposure. Unlikely to occur. However provide symptomatic medical treatment if required.

5. FIRE FIGHTING MEASURES

<i>Extinguishing Media</i>	Not combustible. Select extinguishing agent appropriate to other materials involved.
<i>Special Hazards of Product</i>	Combustion will produce smoke, carbon dioxide and carbon monoxide. See also Section 10.
<i>Protective Equipment for Fire-Fighting</i>	Wear self contained breathing apparatus.



SAFETY DATA SHEET

SikaGard Elastocolor 675W

Date of issue - 09/03/2004.

SGDELS675

6. ACCIDENTAL RELEASE MEASURES

<i>Personal Precautions</i>	Wear appropriate protective clothing.
<i>Environmental Precautions and Clean-up Methods</i>	Try to prevent the material from entering drains or water courses.
<i>Spillages</i>	Contain and absorb using earth, sand or other inert material. Transfer into suitable containers for recovery or disposal.

7. HANDLING AND STORAGE

<i>Handling</i>	Use in well ventilated area. Avoid contact with eyes, skin and clothing. Keep container tightly closed when not in use.
<i>Storage</i>	Storage area should be: cool. dry. Store in original containers. Protect from extremes of cold. Storage temperature should be controlled to between 5 and 25 °C.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

<i>Occupational Exposure Limits</i>	None assigned.
<i>Engineering Control Measures</i>	Use of the basic principles of Industrial Hygiene will enable this material to be used safely.
<i>Respiratory Protection</i>	Respiratory protection not normally required.
<i>Hand Protection</i>	Wear suitable impervious gloves.
<i>Eye Protection</i>	Wear safety glasses if risks of accidental contamination are possible during application.

9. PHYSICAL AND CHEMICAL PROPERTIES

<i>Physical State</i>	Liquid.
<i>Color</i>	Various
<i>Odor</i>	Characteristic.
<i>Flash Point °C</i>	Not applicable.
<i>Solubility - Water</i>	Miscible.
<i>Density (kg/m³)</i>	Approx. 1310 at 20 °C.
<i>Viscosity (at 20°C)</i>	Mobile liquid at ambient temperatures.

10. STABILITY AND REACTIVITY

<i>Stability</i>	Stable under normal conditions.
<i>Conditions to avoid</i>	Protect from frost
<i>Materials to avoid</i>	None under normal conditions.
<i>Hazardous Decomposition Products</i>	After evaporation of water, combustion will generate: oxides of carbon. acrylic monomers, acrid smoke and irritating fumes.



SAFETY DATA SHEET
SikaGard Elastocolor 675W

Date of issue - 09/03/2004.

SGDELS675

11. TOXICOLOGICAL INFORMATION

<i>Acute toxicity</i>	Low order of acute toxicity.
<i>Eye irritation</i>	May cause slight transient irritation.
<i>Skin irritation</i>	Frequent or prolonged skin contact may cause some local short term skin irritation.

12. ECOLOGICAL INFORMATION

<i>Mobility</i>	Mobile liquid. Emulsifiable in water.
<i>Persistence/degradability</i>	The product is partially or slowly biodegradable.
<i>Ecotoxicity</i>	The product may be harmful to aquatic organisms.

13. DISPOSAL

<i>Product Disposal</i>	Arrange for disposal via a licensed waste contractor.
<i>Container Disposal</i>	Dispose of containers with care. Empty packaging should be removed by a licensed waste contractor.

14. TRANSPORT INFORMATION

<i>ADR/RID : Number</i>	Not Regulated under ADR/RID
<i>IMDG : Proper shipping name</i>	Not Regulated under IMDG
<i>IATA : Proper shipping name</i>	Not Regulated under ICAO

15. REGULATORY INFORMATION

<i>Risk Phrases</i>	None assigned.
<i>Safety Phrases</i>	None assigned.

16. OTHER INFORMATION

<i>First Issue Date</i>	9.03.2004
<i>Revisions Highlighted</i>	Future revisions will incorporate such information as is required but which is not available at this time.
<i>Uses and Restrictions</i>	Customers are urged to ensure that the product is entirely suitable for their own purpose. It is the customer's responsibility to ensure that a suitable and sufficient assessment of the risks created by the use of the product is undertaken.
<i>UK Legislation</i>	Health and Safety at Work etc Act, 1974, and relevant Statutory Provisions. SI 2002/1689: Chemicals (Hazard Information and Packaging) Regulations SI 2002/2677: The Control of Substances Hazardous to Health Regulations SI No 2839 1991 Environmental Protection (Duty of Care) Regulations.



SAFETY DATA SHEET
SikaGard Elastocolor 675W

Date of issue - 09/03/2004.

SGDELS675

UK Guidance Publications

General Approved Code of Practice to COSHH Regulations, HSE.

Footnote

The information contained in this SDS corresponds to our level of knowledge at the time of publication. All warranties are excluded. Our most current General Sales Conditions shall apply. Please consult the Technical Data Sheet prior to use.