

**PRODUCT AND COMPANY IDENTIFICATION**

| | |
|------------------------------|--|
| <i>Product Code</i> | ICM52A |
| <i>Product Name</i> | Icoment 520 Part A |
| <i>Product Description</i> | 2-component polymer modified thin layer cementitious render. |
| <i>Manufacturer/Supplier</i> | Sika Limited Watchmead Welwyn Garden City Hertfordshire. AL7 1BQ tel. 01707 394444 Fax. 01707 329129 |

COMPOSITION/INFORMATION ON THE COMPONENTS

| | |
|--|---|
| <i>Hazardous Components in Product</i> | The product does not contain any substances classified as hazardous under current regulations. |
| <i>Chemical Characteristic</i> | Aqueous dispersion of an acrylate copolymer in combination with mineral fillers and plasticisers. |

HAZARD IDENTIFICATION

| | |
|---------------------|------------------------------|
| <i>Main Hazards</i> | Not classified as hazardous. |
|---------------------|------------------------------|

FIRST AID MEASURES

| | |
|---------------------|--|
| <i>Eye Contact</i> | Immediately flood the eye with plenty of water for at least 10 minutes, holding the eye open. Eyelids should be held away from the eyeball to ensure thorough rinsing. Obtain medical attention if soreness or redness persists. |
| <i>Skin Contact</i> | Wash skin thoroughly with soap and water. If material proves difficult to remove, use suitable skin cleanser (not solvent). Contaminated clothing should be washed or dry-cleaned before re-use. |
| <i>Ingestion</i> | Wash out mouth with water. Have victim drink 240-300ml of water. If vomiting occurs naturally, rinse mouth and repeat administration of water. Obtain medical attention. |
| <i>Inhalation</i> | Remove from exposure. Unlikely to occur. However provide symptomatic medical treatment if required. |

FIRE FIGHTING MEASURES

| | |
|---|---|
| <i>Extinguishing Media</i> | Not combustible. Select extinguishing agent appropriate to other materials involved. |
| <i>Special Hazards of Product</i> | Combustion will produce smoke, carbon dioxide and carbon monoxide. |
| <i>Protective Equipment for Fire-Fighting</i> | Wear self contained breathing apparatus. |



SAFETY DATA SHEET

Icoment 520 Part A

Date of issue - 22/03/2001.

ICM52A

ACCIDENTAL RELEASE MEASURES

| | |
|---|--|
| <i>Personal Precautions</i> | Wear appropriate protective clothing. |
| <i>Environmental Precautions and Clean-up Methods</i> | Try to prevent the material from entering drains or water courses. |
| <i>Spillages</i> | Contain and absorb using earth, sand or other inert material. Transfer into suitable containers for recovery or disposal. Small spillages may be flushed with large quantities of water. |

HANDLING AND STORAGE

| | |
|-----------------|--|
| <i>Handling</i> | Use in well ventilated area. Avoid contact with eyes, skin and clothing. Keep container tightly closed when not in use. |
| <i>Storage</i> | Storage area should be: cool, dry. Store in original containers. Protect from extremes of cold. Storage temperature should be controlled to between 5 and 25 °C. |

EXPOSURE CONTROLS/PERSONAL PROTECTION

| | |
|--|--|
| <i>Occupational Exposure Standards</i> | None assigned. |
| <i>Engineering Control Measures</i> | Use of the basic principles of Industrial Hygiene will enable this material to be used safely. |
| <i>Respiratory Protection</i> | Respiratory protection not normally required. |
| <i>Hand Protection</i> | Wear suitable impervious gloves. |
| <i>Eye Protection</i> | Wear safety glasses if risks of accidental contamination are possible during application. |

PHYSICAL AND CHEMICAL PROPERTIES

| | |
|------------------------------------|---|
| <i>Physical State</i> | Viscous liquid. |
| <i>Color</i> | Grey. - Green. |
| <i>Odor</i> | Characteristic. |
| <i>pH</i> | 9.5 (typical) |
| <i>Flash Point °C</i> | Not applicable. |
| <i>Solubility - Water</i> | Emulsifies. |
| <i>Vapor Pressure (kPa)</i> | Approx. 2.0 at 25 °C. |
| <i>Density (kg/m3)</i> | Approx. 1.10 at 20 °C. |
| <i>Autoignition Temperature °C</i> | Not auto-flammable. |
| <i>Viscosity (at 20°C)</i> | Viscous liquid at ambient temperatures. |

STABILITY AND REACTIVITY

| | |
|---|---|
| <i>Stability</i> | Stable under normal conditions. |
| <i>Conditions to avoid</i> | Protect from frost |
| <i>Materials to avoid</i> | None under normal conditions. |
| <i>Hazardous Decomposition Products</i> | After evaporation of water, combustion will generate: oxides of carbon, acrylic monomers, acrid smoke and irritating fumes. |



SAFETY DATA SHEET
Icoment 520 Part A

Date of issue - 22/03/2001.

ICM52A

TOXICOLOGICAL INFORMATION

| | |
|------------------------|---|
| <i>Acute toxicity</i> | Low order of acute toxicity. |
| <i>Eye irritation</i> | May cause slight transient irritation. |
| <i>Skin irritation</i> | Frequent or prolonged skin contact may cause some local short term skin irritation. |

ECOLOGICAL INFORMATION

| | |
|----------------------------------|---|
| <i>Mobility</i> | Mobile liquid. Emulsifiable in water. |
| <i>Persistence/degradability</i> | The product is expected to be readily biodegradable. |
| <i>Bioaccumulative potential</i> | Product is not expected to bioaccumulate. |
| <i>Ecotoxicity</i> | The product is expected to be non-hazardous to aquatic species. |

DISPOSAL

| | |
|---------------------------|---|
| <i>Product Disposal</i> | Arrange for disposal via a licensed waste contractor. |
| <i>Container Disposal</i> | Dispose of containers with care. Containers should be cleaned by appropriate methods and then re-used or disposed of by landfill or incineration as appropriate. Empty packaging should be removed by a licensed waste contractor. |

TRANSPORT INFORMATION

| | |
|------------------------------|------------------------------|
| <i>UN :</i> <i>UN number</i> | Not classified as hazardous. |
| <i>UN :</i> <i>Class</i> | Not listed. |

REGULATORY INFORMATION

| | |
|-----------------------|---|
| <i>Risk Phrases</i> | None assigned. |
| <i>Safety Phrases</i> | The following are considered as advisory. Keep out of reach of children. In case of contact with eyes, rinse immediately with plenty of water and seek medical advice. Wear suitable gloves and eye/face protection. |

OTHER INFORMATION

| | |
|------------------------------|--|
| <i>First Issue Date</i> | 14.11.1995 |
| <i>Revisions Highlighted</i> | Future revisions will incorporate such information as is required but which is not available at this time. |
| <i>Uses and Restrictions</i> | Customers are urged to ensure that the product is entirely suitable for their own purpose. It is the customer's responsibility to ensure that a suitable and sufficient assessment of the risks created by the use of the product is undertaken. |



SAFETY DATA SHEET

Icoment 520 Part A

Date of issue - 22/03/2001.

ICM52A

UK Legislation

Health and Safety at Work etc Act, 1974, and relevant Statutory Provisions.
SI 1993/1746: Chemicals (Hazard Information and Packaging) Regulations, 1993.
SI 1999/437: The Control of Substances Hazardous to Health Regulations
SI No 2839 1991 Environmental Protection (Duty of Care) Regulations.

UK Guidance Publications

General Approved Code of Practice to COSHH Regulations, HSE.

Footnote

The information contained in this SDS corresponds to our level of knowledge at the time of publication. All warranties are excluded. Our most current General Sales Conditions shall apply. Please consult the Technical Data Sheet prior to use.

**PRODUCT AND COMPANY IDENTIFICATION**

| | |
|------------------------------|--|
| Product Code | ICM52B |
| Product Name | Icoment 520 Part B |
| Product Description | 2-component polymer modified thin layer cementitious render. |
| Manufacturer/Supplier | Sika Limited Watchmead Welwyn Garden City Hertfordshire. AL7 1BQ tel. 01707 394444 Fax. 01707 329129 |

COMPOSITION/INFORMATION ON THE COMPONENTS**Preparation - Hazardous ingredients (Europe)**

| Component | Concentration | Classification | Risk Phrases |
|--------------------|----------------------|-----------------------|---------------------|
| 1) Portland Cement | 25.00 - 50.00 % | Xi | R41 |

HAZARD IDENTIFICATION

| | |
|------------------------------------|--|
| Main Hazards | Risk of serious damage to eyes. Dry cement powders in normal use have no harmful effect on the dry skin. However, when cement is mixed with water or becomes damp, alkalis are released which can be harmful. Contact with wet cement or wet mortar may cause irritation, dermatitis or burns. |
| Health Effects - Eyes | Dust will cause conjunctival irritation and possibly corneal damage. |
| Health Effects - Skin | Repeated and/or prolonged contact may lead to dermatitis. Repeated or prolonged contact may cause chemical burns. |
| Health Effects - Inhalation | Exposure to dust at high concentrations may have the following effects:- irritation of nose, throat and respiratory tract. Respirable silica dusts if inhaled over a prolonged period could constitute a health hazard. (see Sect.8) |

FIRST AID MEASURES

| | |
|---------------------|---|
| Eye Contact | Immediately flood the eye with plenty of water for at least 15 minutes, holding the eye open. Obtain medical attention urgently. |
| Skin Contact | Wash skin thoroughly with soap and water. Obtain medical attention if blistering occurs or redness persists. Contaminated clothing should be washed or dry-cleaned before re-use. |
| Ingestion | Do not induce vomiting. Wash out mouth with water. |
| Inhalation | Remove from exposure. In cases of possible respiratory irritation or if feeling unwell in cases of prolonged exposure, obtain medical attention. |



SAFETY DATA SHEET

Icoment 520 Part B

Date of issue - 22/03/2001.

ICM52B

FIRE FIGHTING MEASURES

Extinguishing Media

Not combustible.
Select extinguishing agent appropriate to other materials involved.

ACCIDENTAL RELEASE MEASURES

Personal Precautions

Wear appropriate protective clothing.

Spillages

Avoid creating a dust.
Sweep up into suitable containers for recovery or disposal.

HANDLING AND STORAGE

Handling

Avoid inhaling dust.
Exposure by inhalation or skin contact should be minimised by good Industrial Hygiene practices.
Use in well ventilated area.

Storage

Storage area should be: cool. dry.

EXPOSURE CONTROLS/PERSONAL PROTECTION

Occupational Exposure Limits - GB

1) Portland Cement

UK EH40: OES 10mg/m³ 8h TWA. Dust, total inhalable:
UK EH40: OES 5mg/m³ 8h TWA. Dust, respirable:

Engineering Control Measures

Use of the basic principles of Industrial Hygiene will enable this material to be used safely.
Every effort should be made to prevent airborne dusts arising during mixing operations.

Respiratory Protection

If limits are exceeded use an approved dust mask.

Hand Protection

Wear suitable impervious gloves.

Eye Protection

Dust tight goggles.

Body Protection

Protective clothing should be worn which ensures that cementitious materials do not come into contact with the skin. Particular care should be taken to ensure that wet mortar does not enter boots/footwear.

PHYSICAL AND CHEMICAL PROPERTIES

Physical State

Powder.

Color

Grey.

Odor

None.

pH

Approx. 12 in water.

Flash Point °C

Not applicable.

Explosion Limits (%)

Not determined.

Solubility - Water

Partially soluble.

Density (kg/m³)

Approx. 1.6. (loose)



SAFETY DATA SHEET

Icoment 520 Part B

Date of issue - 22/03/2001.

ICM52B

STABILITY AND REACTIVITY

| | |
|---|---------------------------------|
| <i>Stability</i> | Stable under normal conditions. |
| <i>Materials to avoid</i> | Strong mineral acids. |
| <i>Hazardous Decomposition Products</i> | None known. |

TOXICOLOGICAL INFORMATION

| | |
|------------------------|---|
| <i>Acute toxicity</i> | Low order of acute toxicity. |
| <i>Eye irritation</i> | Cement is a severe eye irritant. Gross exposures or untreated mild exposures can lead to chemical burning and ulceration of the eye. |
| <i>Skin irritation</i> | Cement and/or water/cement mixtures may cause irritant contact dermatitis, allergic (chromium) dermatitis, and/or burns. |

ECOLOGICAL INFORMATION

| | |
|----------------------------------|---|
| <i>Mobility</i> | The product is sparingly soluble in water. |
| <i>Persistence/degradability</i> | Inorganic basis, therefore non biodegradable. |
| <i>Bioaccumulative potential</i> | Product is not expected to bioaccumulate. |
| <i>Ecotoxicity</i> | The product is expected to be non-hazardous to aquatic species. |

DISPOSAL

| | |
|---------------------------|--|
| <i>Product Disposal</i> | As an inert material it may be disposed of via an approved solid waste disposal facility. |
| <i>Container Disposal</i> | Empty packaging may be disposed along with normal builders waste via an authorised waste contractor. |

TRANSPORT INFORMATION

| | |
|--|--|
| <i>UN : UN number</i> | Not classified as dangerous for transport. |
| <i>ADR/RID Substance Identification Number</i> | Not classified. |
| <i>ADR/RID Proper shipping name</i> | Not listed. |
| <i>IMDG : Proper shipping name</i> | Not classified. |
| <i>IATA : Proper shipping name</i> | Not classified. |

REGULATORY INFORMATION

Label Requirements

Irritant



Risk Phrases

Risk of serious damage to eyes.

BCA recommended risk phrases:
Contact with wet cement, wet concrete or wet mortar may cause irritation, dermatitis or burns.
Contact between cement powder and body fluids (eg sweat and eye fluid) may also cause irritation, dermatitis or burns.



SAFETY DATA SHEET
Icoment 520 Part B

Date of issue - 22/03/2001.

ICM52B

Safety Phrases

Keep out of reach of children.
In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
After contact with skin, wash immediately with plenty of: soap and water.
Wear suitable protective clothing, gloves and eye/face protection.

OTHER INFORMATION

First Issue Date

14.11.1995

Revisions Highlighted

Future revisions will incorporate such information as is required but which is not available at this time.

Uses and Restrictions

Customers are urged to ensure that the product is entirely suitable for their own purpose. It is the customer's responsibility to ensure that a suitable and sufficient assessment of the risks created by the use of the product is undertaken.

UK Legislation

Health and Safety at Work etc Act, 1974, and relevant Statutory Provisions.
SI 1993/1746: Chemicals (Hazard Information and Packaging) Regulations, 1993.
SI 1999/437: The Control of Substances Hazardous to Health Regulations
SI No 2839 1991 Environmental Protection (Duty of Care) Regulations.

UK Guidance Publications

General Approved Code of Practice to COSHH Regulations, HSE.
EH40, Occupational Exposure Limits, HSE. Revised Annually.
EH44, Dust in the Workplace: General Principles of Protection, HSE.
EH26, Occupational Skin Diseases: Health and Safety Precautions, HSE.
CONIAC Health Hazard Information Sheet No.26 (Cement)

Footnote

The information contained in this SDS corresponds to our level of knowledge at the time of publication. All warranties are excluded. Our most current General Sales Conditions shall apply. Please consult the Technical Data Sheet prior to use.